



### Ángulo estructural lados iguales

DADO No.	A Pulgadas	B Pulgadas	T Pulgadas	R Pulgadas	R1 Pulgadas	PESO Lb/Ft	PESO Kg/m	6061 T-6
850	0.750	0.750	0.125	0.125	0.093	0.201	0.299	OK
801	1.000	1.000	0.125	0.125	0.093	0.275	0.410	OK
50284	1.000	1.000	0.188	0.125	0.094	0.400	0.596	OK
791	1.000	1.000	0.250	0.125	0.093	0.397	0.768	OK
802	1.250	1.250	0.125	0.187	0.125	0.350	0.522	OK
1013	1.250	1.250	0.187	0.187	0.125	0.509	0.758	OK
855	1.250	1.250	0.250	0.187	0.125	0.662	0.985	OK
792	1.500	1.500	0.125	0.187	0.125	0.424	0.630	OK
793	1.500	1.500	0.187	0.187	0.125	0.619	0.922	OK
766	1.500	1.500	0.250	0.187	0.125	0.809	1.204	OK
50260	1.750	1.750	0.125	0.187	0.125	0.497	0.740	OK
767	2.000	2.000	0.125	0.250	0.125	0.577	0.860	OK
768	2.000	2.000	0.187	0.250	0.125	0.846	1.260	OK
794	2.000	2.000	0.250	0.250	0.125	1.110	1.652	OK
807	2.000	2.000	0.375	0.250	0.125	1.606	2.390	OK
804	2.500	2.500	0.188	0.250	0.125	1.066	1.587	OK
50259	2.500	2.500	0.125	0.250	0.125	0.724	1.078	OK
795	2.500	2.500	0.250	0.250	0.125	1.404	2.090	OK
995	2.500	2.500	0.375	0.250	0.125	2.047	3.047	OK
796	3.000	3.000	0.187	0.312	0.250	1.275	1.900	OK
797	3.000	3.000	0.250	0.312	0.250	1.683	2.505	OK
834	3.000	3.000	0.375	0.312	0.250	2.473	3.681	OK
816	3.000	3.000	0.500	0.312	0.250	3.227	4.802	OK
769	3.500	3.500	0.250	0.375	0.250	1.988	2.959	OK
770	4.000	4.000	0.250	0.375	0.250	2.282	3.397	OK
771	4.000	4.000	0.375	0.375	0.250	3.366	5.010	OK
839	4.000	4.000	0.500	0.375	0.250	4.414	6.568	OK
851	6.000	6.000	0.375	0.500	0.375	5.226	7.643	OK
840	6.000	6.000	0.500	0.500	0.375	6.753	10.840	OK

Especificación Federal: QQ-A-200/9, 6063-T5/QQ-a-200/8, 6061-T6