



### Ángulo estructural lados desiguales

DADO No.	A Pulgadas	B Pulgadas	T Pulgadas	R Pulgadas	R1 Pulgadas	PESO Lb/Ft	PESO Kg/m	6061 T-6
50060	1.500	1.250	0.125	0.188	0.125	0.386	0.575	OK
50061	1.500	1.250	0.188	0.188	0.125	0.567	0.844	OK
50062	1.750	1.250	0.125	0.188	0.125	0.424	0.630	OK
50063	1.750	1.250	0.250	0.188	0.125	0.810	1.205	OK
50154	2.000	1.000	0.125	0.188	0.125	0.424	0.630	OK
50064	2.000	1.500	0.125	0.188	0.125	0.497	0.740	OK
50065	2.000	1.500	0.188	0.188	0.125	0.733	1.091	OK
825	2.000	1.500	0.250	0.188	0.125	0.957	1.423	OK
18520	2.500	1.500	0.250	0.250	0.125	1.110	1.652	OK
50139	2.500	2.000	0.187	0.250	0.125	0.956	1.423	OK
50080	2.500	2.000	0.375	0.250	0.125	1.827	2.719	OK
967	3.000	2.000	0.188	0.312	0.188	1.071	1.593	OK
772	3.000	2.000	0.250	0.312	0.188	1.403	2.088	OK
50280	3.000	2.000	0.375	0.312	0.188	2.046	3.045	OK
50067	3.000	2.500	0.250	0.312	0.250	1.537	2.287	OK
50068	3.000	2.500	0.375	0.312	0.250	2.253	3.353	OK
50002	3.500	2.500	0.250	0.312	0.250	1.684	2.506	OK
50070	3.500	3.000	0.250	0.375	0.250	1.841	2.740	OK
50073	4.000	2.000	0.187	0.312	0.187	1.289	1.918	OK
814	4.000	3.000	0.250	0.375	0.250	1.988	2.959	OK
50072	4.000	3.000	0.500	0.375	0.250	3.826	5.694	OK
50074	5.000	3.000	0.500	0.375	0.312	4.396	6.568	OK
50075	5.000	3.500	0.312	0.437	0.312	3.003	4.469	OK
50077	5.000	3.500	0.500	0.437	0.312	4.703	6.999	OK
4657	6.000	3.500	0.312	0.500	0.312	3.385	5.038	OK
50078	6.000	3.500	0.500	0.500	0.312	5.306	7.896	OK
815	6.000	4.000	0.375	0.500	0.375	4.237	6.305	OK
50079	6.000	4.000	0.500	0.500	0.375	5.578	8.301	OK
50047	8.000	6.000	0.625	0.500	0.313	9.844	14.650	OK

Especificación Federal: QQ-A-200/9, 6063-T5/QQ-a-200/8, 6061-T6