


# ASL Catalogue




## RECTANGULAR BAR (SHARP CORNERS)

| DIE No. | A Inches | B Inches | WEIGHT Lb/Ft | WEIGHT Kg/m | 6061 T-6 |
|---------|----------|----------|--------------|-------------|----------|
| 1202    | 0.062    | 1.000    | 0.073        | 0.109       |          |
| 18481   | 0.062    | 1.500    | 0.109        | 0.163       |          |
| 1258    | 0.080    | 2.875    | 0.270        | 0.403       |          |
| 50045   | 0.094    | 1.000    | 0.110        | 0.165       |          |
| 50089   | 0.098    | 0.500    | 0.057        | 0.085       |          |
| 50085   | 0.098    | 0.750    | 0.087        | 0.128       |          |
| 50088   | 0.098    | 1.000    | 0.115        | 0.171       |          |
| 11473   | 0.100    | 3.875    | 0.453        | 0.678       |          |
| 18040   | 0.125    | 0.375    | 0.055        | 0.082       |          |
| 1203    | 0.125    | 0.500    | 0.073        | 0.109       |          |
| 17572   | 0.125    | 0.625    | 0.092        | 0.137       |          |
| 18028   | 0.125    | 0.750    | 0.110        | 0.164       |          |
| 1205    | 0.125    | 1.000    | 0.147        | 0.219       | OK       |
| 17574   | 0.125    | 1.250    | 0.184        | 0.273       | OK       |
| 1207    | 0.125    | 1.500    | 0.220        | 0.328       | OK       |
| 19094   | 0.125    | 1.750    | 0.257        | 0.383       | OK       |
| 61077   | 0.125    | 1.875    | 0.276        | 0.410       | OK       |
| 17576   | 0.125    | 2.000    | 0.294        | 0.438       | OK       |
| 18041   | 0.125    | 3.000    | 0.441        | 0.656       | OK       |
| 1245    | 0.125    | 3.875    | 0.570        | 0.847       | OK       |
| 17687   | 0.125    | 4.000    | 0.588        | 0.875       | OK       |
| 1251    | 0.125    | 5.000    | 0.735        | 1.094       | OK       |
| 17609   | 0.125    | 6.000    | 0.882        | 1.313       | OK       |
| 50133   | 0.125    | 6.125    | 0.900        | 1.340       | OK       |
| 19761   | 0.156    | 0.500    | 0.092        | 0.137       | OK       |
| 17578   | 0.187    | 0.500    | 0.110        | 0.164       | OK       |
| 17579   | 0.187    | 0.625    | 0.137        | 0.205       | OK       |
| 1211    | 0.187    | 0.750    | 0.165        | 0.245       | OK       |
| 18091   | 0.187    | 1.000    | 0.220        | 0.327       | OK       |
| 17580   | 0.187    | 1.250    | 0.275        | 0.409       | OK       |
| 17083   | 0.187    | 1.500    | 0.330        | 0.491       | OK       |
| 17084   | 0.187    | 1.750    | 0.385        | 0.573       | OK       |

Federal Specification: QQ-A-200/9, 6063-T5/QQ-a-200/8, 6061-T6

# ASL Catalogue




## RECTANGULAR BAR (SHARP CORNERS)

| DIE No. | A Inches | B Inches | WEIGHT Lb/Ft | WEIGHT Kg/m | 6061 T-6 |
|---------|----------|----------|--------------|-------------|----------|
| 1216    | 0.187    | 2.000    | 0.447        | 0.665       | OK       |
| 17086   | 0.187    | 2.500    | 0.550        | 0.818       | OK       |
| 1218    | 0.187    | 3.000    | 0.660        | 0.988       | OK       |
| 18581   | 0.187    | 3.000    | 0.660        | 0.982       | OK       |
| 17692   | 0.187    | 4.000    | 0.880        | 1.309       | OK       |
| 61459   | 0.187    | 5.000    | 1.106        | 1.646       | OK       |
| 17582   | 0.250    | 0.500    | 0.147        | 0.219       | OK       |
| 17583   | 0.250    | 0.625    | 0.184        | 0.273       | OK       |
| 17584   | 0.250    | 0.750    | 0.220        | 0.328       | OK       |
| 50135   | 0.250    | 0.875    | 0.257        | 0.382       | OK       |
| 17980   | 0.250    | 1.000    | 0.294        | 0.438       | OK       |
| 17585   | 0.250    | 1.250    | 0.367        | 0.546       | OK       |
| 17981   | 0.250    | 1.500    | 0.441        | 0.656       | OK       |
| 17587   | 0.250    | 1.750    | 0.514        | 0.766       | OK       |
| 17708   | 0.250    | 2.000    | 0.588        | 0.875       | OK       |
| 17588   | 0.250    | 2.500    | 0.735        | 1.094       | OK       |
| 17589   | 0.250    | 3.000    | 0.882        | 1.313       | OK       |
| 17590   | 0.250    | 3.500    | 1.060        | 1.537       | OK       |
| 17591   | 0.250    | 4.000    | 1.176        | 1.755       | OK       |
| 17106   | 0.250    | 5.000    | 1.470        | 2.188       | OK       |
| 50018   | 0.250    | 5.500    | 1.617        | 2.406       | OK       |
| 17592   | 0.250    | 6.000    | 1.764        | 2.625       | OK       |
| 4233    | 0.250    | 8.000    | 2.352        | 3.500       | OK       |
| 50116   | 0.250    | 12.000   | 3.528        | 5.250       | OK       |
| 19095   | 0.375    | 0.750    | 0.331        | 0.494       | OK       |
| 17593   | 0.375    | 1.000    | 0.443        | 0.659       | OK       |
| 17594   | 0.375    | 1.250    | 0.552        | 0.821       | OK       |
| 17595   | 0.375    | 1.500    | 0.661        | 0.984       | OK       |
| 17610   | 0.375    | 1.750    | 0.771        | 1.152       | OK       |
| 17088   | 0.375    | 2.000    | 0.882        | 1.312       | OK       |
| 17596   | 0.375    | 2.500    | 1.102        | 1.640       | OK       |
| 17089   | 0.375    | 3.000    | 1.323        | 1.969       | OK       |
| 17628   | 0.375    | 4.000    | 1.764        | 2.625       | OK       |

Federal Specification: QQ-A-200/9, 6063-T5/QQ-a-200/8, 6061-T6

# ASL Catalogue




## RECTANGULAR BAR (SHARP CORNERS)

| DIE No. | A Inches | B Inches | WEIGHT Lb/Ft | WEIGHT Kg/m | 6061 T-6 |
|---------|----------|----------|--------------|-------------|----------|
| 4363    | 0.375    | 5.000    | 2.205        | 3.281       | OK       |
| 17622   | 0.375    | 6.000    | 2.646        | 3.938       | OK       |
| 17655   | 0.375    | 8.000    | 3.528        | 5.250       | OK       |
| 50267   | 0.375    | 10.000   | 4.410        | 6.563       | OK       |
| 17683   | 0.500    | 0.625    | 0.367        | 0.547       | OK       |
| 17090   | 0.500    | 1.000    | 0.588        | 0.875       | OK       |
| 17613   | 0.500    | 1.250    | 0.735        | 1.094       | OK       |
| 17597   | 0.500    | 1.500    | 0.882        | 1.313       | OK       |
| 17091   | 0.500    | 2.000    | 1.176        | 1.750       | OK       |
| 17615   | 0.500    | 2.500    | 1.470        | 2.187       | OK       |
| 17092   | 0.500    | 3.000    | 1.764        | 2.625       | OK       |
| 17666   | 0.500    | 3.500    | 2.058        | 3.063       | OK       |
| 1241    | 0.500    | 4.000    | 2.352        | 3.500       | OK       |
| 4283    | 0.500    | 5.000    | 2.940        | 4.375       | OK       |
| 17094   | 0.500    | 6.000    | 3.528        | 5.250       | OK       |
| 50117   | 0.500    | 7.000    | 4.116        | 6.125       | OK       |
| 17698   | 0.500    | 8.000    | 4.704        | 7.000       | OK       |
| 18813   | 0.500    | 10.000   | 5.880        | 8.750       | OK       |
| 18814   | 0.500    | 12.000   | 7.056        | 10.500      | OK       |
| 61505   | 0.625    | 2.750    | 2.021        | 3.008       | OK       |
| 17616   | 0.750    | 1.000    | 0.882        | 1.313       | OK       |
| 17095   | 0.750    | 1.500    | 1.322        | 1.976       | OK       |
| 17618   | 0.750    | 2.000    | 1.764        | 2.625       | OK       |
| 17629   | 0.750    | 3.000    | 2.646        | 3.938       | OK       |
| 17630   | 0.750    | 3.500    | 3.087        | 4.594       | OK       |
| 17103   | 0.750    | 4.000    | 3.528        | 5.250       | OK       |
| 17647   | 0.750    | 6.000    | 5.292        | 7.875       | OK       |
| 4378    | 0.750    | 8.000    | 7.056        | 10.500      | OK       |
| 50290   | 0.750    | 12.000   | 10.584       | 15.751      | OK       |
| 18014   | 1.000    | 1.500    | 1.764        | 2.625       | OK       |
| 17602   | 1.000    | 2.000    | 2.352        | 3.500       | OK       |
| 17659   | 1.000    | 2.500    | 2.940        | 4.375       | OK       |
| 17627   | 1.000    | 3.000    | 3.528        | 5.250       | OK       |
| 17636   | 1.000    | 4.000    | 4.704        | 7.000       | OK       |
| 17096   | 1.000    | 5.000    | 5.880        | 8.750       | OK       |
| 17097   | 1.000    | 6.000    | 7.056        | 10.500      | OK       |
| 50011   | 1.000    | 7.000    | 8.232        | 12.251      | OK       |

Federal Specification: QQ-A-200/9, 6063-T5/QQ-a-200/8, 6061-T6

# ASL Catalogue



## RECTANGULAR BAR (SHARP CORNERS)

| DIE No. | A Inches | B Inches | WEIGHT Lb/Ft | WEIGHT Kg/m | 6061 T-6 |
|---------|----------|----------|--------------|-------------|----------|
| 17772   | 1.000    | 8.000    | 9.408        | 14.001      | OK       |
| 17637   | 1.250    | 1.500    | 2.205        | 3.281       | OK       |
| 17679   | 1.250    | 1.750    | 2.572        | 3.828       | OK       |
| 17669   | 1.250    | 2.500    | 3.675        | 5.469       | OK       |
| 17678   | 1.250    | 4.000    | 5.880        | 8.750       | OK       |
| 50095   | 1.250    | 4.500    | 6.581        | 9.844       | OK       |
| 17631   | 1.500    | 2.000    | 3.675        | 5.469       | OK       |
| 17643   | 1.500    | 3.000    | 5.292        | 7.875       | OK       |
| 4394    | 1.500    | 3.500    | 6.174        | 9.188       | OK       |
| 17644   | 1.500    | 4.000    | 7.056        | 10.535      | OK       |
| 17857   | 1.500    | 6.000    | 10.584       | 15.750      | OK       |
| 43991   | 2.000    | 3.000    | 7.056        | 10.500      | OK       |
| 50293   | 2.000    | 3.500    | 7.056        | 10.500      | OK       |
| 17635   | 2.000    | 4.000    | 9.408        | 14.000      | OK       |
| 17663   | 2.500    | 3.000    | 8.820        | 13.125      | OK       |

Federal Specification: QQ-A-200/9, 6063-T5/QQ-a-200/8, 6061-T6

# ASL Catalogue



## RECTANGULAR BAR (ROUNDED CORNERS)

| DIE No. | A Inches | B Inches | R Inches | WEIGHT Lb/Ft | WEIGHT Kg/m | 6061 T-6 |
|---------|----------|----------|----------|--------------|-------------|----------|
| 19081   | 0.062    | 2.000    | 0.031    | 0.145        | 0.216       |          |
| 11322   | 0.125    | 0.750    | 0.062    | 0.108        | 0.158       |          |
| 4171    | 0.125    | 2.000    | 0.062    | 0.290        | 0.432       | OK       |
| 50189   | 0.125    | 2.500    | 0.062    | 0.363        | 0.540       | OK       |
| 50198   | 0.125    | 2.625    | 0.062    | 0.382        | 0.569       | OK       |
| 50187   | 0.187    | 1.500    | 0.093    | 0.320        | 0.476       | OK       |
| 50188   | 0.187    | 2.000    | 0.093    | 0.431        | 0.642       | OK       |
| 50191   | 0.187    | 2.500    | 0.093    | 0.541        | 0.805       | OK       |
| 18638   | 0.250    | 2.750    | 0.125    | 0.833        | 1.215       | OK       |

|       |       |       |       |       |       |    |
|-------|-------|-------|-------|-------|-------|----|
| 17350 | 0.250 | 3.000 | 0.125 | 0.866 | 1.290 | OK |
| 50190 | 0.313 | 3.500 | 0.157 | 1.264 | 1.881 | OK |
| 4035  | 0.375 | 1.500 | 0.188 | 0.646 | 0.961 | OK |

Federal Specification: QQ-A-200/9, 6063-T5/AA-200/8, 6061-T6

[www.cuprumextrusions.com](http://www.cuprumextrusions.com)

[www.cuprumextrusions.com](http://www.cuprumextrusions.com)

---

[www.cuprumextrusions.com](http://www.cuprumextrusions.com)

---

[www.cuprumextrusions.com](http://www.cuprumextrusions.com)

---

[www.cuprumextrusions.com](http://www.cuprumextrusions.com)

