


RECTANGULAR TUBE (SHARP CORNERS)

DIE No.	A Inches	B Inches	T Inches	WEIGHT Lb/Ft	WEIGHT Kg/m	6061 T-6
50034	0.500	0.750	0.050	0.138	0.201	
22049	0.500	1.000	0.062	0.201	0.299	
2500	0.500	1.000	0.065	0.209	0.312	
22284	0.500	1.000	0.125	0.376	0.547	OK
11086	0.750	1.500	0.045	0.229	0.340	
2515	0.750	1.500	0.050	0.253	0.376	
2523	0.750	1.750	0.052	0.298	0.437	
50180	0.750	1.750	0.052	0.293	0.436	
50200	1.000	1.375	0.073	0.383	0.570	
2514	1.000	1.500	0.062	0.346	0.516	
22285	1.000	1.500	0.125	0.661	0.984	OK
19367	1.000	1.750	0.039	0.245	0.365	
11121	1.000	2.000	0.050	0.341	0.508	
2521	1.000	2.000	0.057	0.387	0.576	
50177	1.000	2.000	0.065	0.439	0.653	
50199	1.000	2.000	0.073	0.490	0.729	
50178	1.000	2.000	0.083	0.553	0.823	
22272	1.000	2.000	0.125	0.808	1.203	OK
50209	1.000	2.000	0.188	1.160	1.727	OK
22242	1.000	3.000	0.060	0.548	0.815	
2516	1.000	3.000	0.083	0.748	1.114	
22286	1.000	3.000	0.125	1.102	1.641	OK
22161	1.000	4.000	0.072	0.822	1.224	
50252	1.000	4.000	0.078	0.889	1.322	
50028	1.000	4.000	0.125	1.424	2.077	OK
50094	1.000	4.000	0.188	2.040	3.035	OK
11099	1.250	2.500	0.055	0.471	0.701	
2513	1.250	2.500	0.062	0.529	0.787	
14302	1.500	1.750	0.070	0.512	0.762	
50023	1.500	2.000	0.090	0.699	1.046	
15052	1.500	2.000	0.125	0.955	1.422	OK
11084	1.500	3.000	0.060	0.618	0.920	

Federal Specification: QQ-A-200/9, 6063-T5/AA-QQ-a-200/8, 6061-T6



RECTANGULAR TUBE (SHARP CORNERS)

DIE No.	A Inches	B Inches	T Inches	WEIGHT Lb/Ft	WEIGHT Kg/m	6061 T-6
22134	1.500	3.000	0.070	0.718	1.068	
2509	1.500	3.000	0.083	0.847	1.260	
50203	1.750	2.250	0.125	1.102	1.641	
19613	1.750	3.000	0.050	0.547	0.814	
11122	1.750	3.000	0.058	0.632	0.941	
22026	1.750	3.000	0.075	0.811	1.208	
2522	1.750	3.000	0.078	0.843	1.254	
22282	1.750	3.000	0.125	1.323	1.969	OK
14729	1.750	4.000	0.060	0.791	1.183	
50027	1.750	4.000	0.067	0.903	1.345	
2520	1.750	4.000	0.078	1.026	1.527	
22107	1.750	4.000	0.109	1.418	2.111	OK
22017	1.750	4.000	0.125	1.617	2.406	OK
22273	2.000	3.000	0.125	1.396	2.078	OK
2329	2.000	3.000	0.250	2.646	3.938	OK
50114	2.000	4.000	0.070	0.965	1.436	
2518	2.000	4.000	0.109	1.482	2.206	OK
22288	2.000	4.000	0.125	1.690	2.516	OK
50285	2.000	4.000	0.188	2.487	3.701	OK
2335	2.000	5.000	0.125	1.984	2.953	OK
2529	2.000	6.000	0.125	2.278	3.391	OK
19742	2.000	8.000	0.125	2.876	4.280	OK
50092	4.000	6.000	0.188	4.245	6.317	OK
50016	4.000	6.000	0.250	5.586	8.313	OK

Federal Specification: QQ-A-200/9, 6063-T5/AA-a-200/8, 6061-T6

ASL Catalogue



RECTANGULAR TUBE (ROUNDED CORNERS)

DIE No.	A Inches	B Inches	T Inches	R1 Inches	R2 Inches	WEIGHT Lb/Ft	WEIGHT Kg/m	6061 T-6
22051	0.500	1.000	0.065	0.062	0.031	0.210	0.312	
12292	0.750	1.000	0.040	0.093	0.053	0.154	0.230	
22019	1.000	2.000	0.065	0.125	0.062	0.433	0.645	
18022	1.000	2.000	0.083	0.098	0.015	0.542	0.809	
18129	1.000	2.000	0.125	0.125	0.031	0.824	1.181	OK
2652	1.250	2.500	0.052	0.250	0.198	0.423	0.629	

50182	1.375	3.000	0.120	0.180	0.060	1.163	1.730	OK
50181	1.500	3.000	0.083	0.062	0.015	0.840	1.250	
22053	1.500	3.000	0.090	0.340	0.250	0.865	1.287	OK
22387	1.750	3.000	0.075	0.125	0.062	0.806	0.200	
19552	4.000	6.000	0.250	0.437	0.187	5.447	8.105	OK
50012	4.000	8.000	0.187	0.187	0.375	5.020	7.471	OK

Federal Specification: QQ-A-200/9, 6063-T5/QQ-a-200/8, 6061-T6

www.cuprumextrusions.com